



## SOTTOVUOTO A BARRA SALDANTE INOX E ABS

INOX AND ABS SEALING BAR VACUUM MACHINE


- Apparecchio per uso professionale (inox) per uso domestico o semi professionale (ABS)
  - Ideale per macellerie, pescherie, ristorazione, mense, industrie della carne e del pesce congelato, hotel, bar, casa
  - Struttura in plastica o in acciaio inox AISI 304
  - Aspirazione esterna ad azione manuale
  - Elettrovalvola di fine ciclo
  - Vacuometro a lancetta con indicazione del tempo reale
  - Comandi digitali
  - Possibilità di usare sia buste lisce che goffrate
  - Pompa per vuoto auto lubrificata che non richiede manutenzione
  - Controllo elettronico del ciclo
  - Scheda elettronica
  - Tensione 220
  - Norme CE
  - Fabbricato in Italia
- *Professional equipment (s/steel) for home or semi-professional use (ABS)*
  - *Particularly suited for butcheries, fish shops, restaurants, canteens, frozen fish meat industries, hotel, bar, home*
  - *Structured in plastic or grade AISI 304 s/steel*
  - *Manual external suction*
  - *Cycle ending electric valve*
  - *Needle Vacuum measurer*
  - *Digital display control*
  - *Suitable for smooth and embossed vacuum bags*
  - *Self-lubricated Vacuum pump that won't require routine maintenance*
  - *Electronic process control*
  - *Electronic control board*
  - *220 voltage*
  - *CE approved*
  - *Proudly Made in Italy*

GUARDA IL VIDEO  
WATCH THE VIDEO



## FSV 33 IF

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230 / 50-60
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,38 (0,50)
<b>Barra saldante</b> <i>Sealing bar (mm)</i>	330
<b>Pompa per vuoto</b> <i>Vacuum pump (L/min)</i>	13
<b>Struttura</b> <i>Structured in</i>	INOX
<b>Peso netto</b> <i>Net weight (kg)</i>	6,0
<b>Peso lordo</b> <i>Gross weight (kg)</i>	8,0
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 420 D. 350 H. 200




DIMENSIONE  
PRODOTTO

B. 390 mm  
D. 300 mm  
H. 180 mm



## FSV 33 IS

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230 / 50-60
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,38 (0,50)
<b>Barra saldante</b> <i>Sealing bar (mm)</i>	330
<b>Pompa per vuoto</b> <i>Vacuum pump (L/min)</i>	13
<b>Struttura</b> <i>Structured in</i>	INOX
<b>Peso netto</b> <i>Net weight (kg)</i>	5,7
<b>Peso lordo</b> <i>Gross weight (kg)</i>	7,0
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 420 D. 350 H. 200




DIMENSIONE  
PRODOTTO

B. 390 mm  
D. 300 mm  
H. 180 mm



## FSV 32T

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230/50
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,4 (0,55)
<b>Barra saldante</b> <i>Sealing bar (mm)</i>	330
<b>Pompa per vuoto</b> <i>Vacuum pump (L/min)</i>	15 - autolubrificata
<b>Struttura</b> <i>Structured in</i>	ABS
<b>Peso netto</b> <i>Net weight (kg)</i>	5,0
<b>Peso lordo</b> <i>Gross weight (kg)</i>	5,5
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 390 D. 330 H. 190




DIMENSIONE  
PRODOTTO

B. 370 mm  
D. 300 mm  
H. 160 mm



## FSV 32IT

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230 / 50-60
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,4 (0,55)
<b>Barra saldante</b> <i>Sealing bar (mm)</i>	330
<b>Pompa per vuoto</b> <i>Vacuum pump (L/min)</i>	15 - autolubrificata
<b>Struttura</b> <i>Structured in</i>	INOX
<b>Peso netto</b> <i>Net weight (kg)</i>	7,0
<b>Peso lordo</b> <i>Gross weight (kg)</i>	7,5
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 390 D. 330 H. 190




DIMENSIONE  
PRODOTTO

B. 360 mm  
D. 290 mm  
H. 150 mm



## FSV 35IT

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230/50
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,4 (0,55)
<b>Barra saldante</b> <i>Sealing bar (mm)</i>	380
<b>Pompa per vuoto</b> <i>Vacuum pump (L/min)</i>	16
<b>Struttura</b> <i>Structured in</i>	INOX
<b>Peso netto</b> <i>Net weight (kg)</i>	8,0
<b>Peso lordo</b> <i>Gross weight (kg)</i>	9,0
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 510 D. 320 H. 210




DIMENSIONE  
PRODOTTO

B. 425 mm  
D. 260 mm  
H. 150 mm

## FSV 45IT

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230/50
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,5 (0,70)
<b>Barra saldante</b> <i>Sealing bar (mm)</i>	430
<b>Pompa per vuoto</b> <i>Vacuum pump (L/min)</i>	25 - autolubrificata
<b>Struttura</b> <i>Structured in</i>	INOX
<b>Peso netto</b> <i>Net weight (kg)</i>	10,0
<b>Peso lordo</b> <i>Gross weight (kg)</i>	11,0
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 610 D. 330 H. 210




DIMENSIONE  
PRODOTTO

B. 480 mm  
D. 240 mm  
H. 140 mm

## FSV 521T

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230 / 50-60
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,55 (0,75)
<b>Barra saldante</b> <i>Sealing bar (mm)</i>	550
<b>Pompa per vuoto</b> <i>Vacuum pump (L/min)</i>	30 - autolubrificata
<b>Struttura</b> <i>Structured in</i>	INOX
<b>Peso netto</b> <i>Net weight (kg)</i>	24,0
<b>Peso lordo</b> <i>Gross weight (kg)</i>	26,0
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 770 D. 280 H. 290



DIMENSIONE  
PRODOTTO

B. 600 mm  
D. 310 mm  
H. 160 mm

