



SOTTOVUOTO A BARRA SALDANTE INOX E ABS

INOX AND ABS SEALING BAR VACUUM MACHINE


- Apparecchio per uso professionale (inox) per uso domestico o semi professionale (ABS)
 - Ideale per macellerie, pescherie, ristorazione, mense, industrie della carne e del pesce congelato, hotel, bar, casa
 - Struttura in plastica o in acciaio inox AISI 304
 - Aspirazione esterna ad azione manuale
 - Elettrovalvola di fine ciclo
 - Vacuometro a lancetta con indicazione del tempo reale
 - Comandi digitali
 - Possibilità di usare sia buste lisce che goffrate
 - Pompa per vuoto auto lubrificata che non richiede manutenzione
 - Controllo elettronico del ciclo
 - Scheda elettronica
 - Tensione 220
 - Norme CE
 - Fabbricato in Italia
- Professional equipment (s/steel) for home or semi-professional use (ABS)
 - Particularly suited for butcheries, fish shops, restaurants, canteens, frozen fish meat industries, hotel, bar, home
 - Structured in plastic or grade AISI 304 s/steel
 - Manual external suction
 - Cycle ending electric valve
 - Needle Vacuum measurer
 - Digital display control
 - Suitable for smooth and embossed vacuum bags
 - Self-lubricated Vacuum pump that won't require routine maintenance
 - Electronic process control
 - Electronic control board
 - 220 voltage
 - CE approved
 - Proudly Made in Italy

GUARDA IL VIDEO
WATCH THE VIDEO



FSV 33 IF

Alimentazione <i>Power supply (Volt/Hz)</i>	230 / 50-60
Potenza <i>Motor power (Kwatt/Hp)</i>	0,38 (0,50)
Barra saldante <i>Sealing bar (mm)</i>	330
Pompa per vuoto <i>Vacuum pump (L/min)</i>	13
Struttura <i>Structured in</i>	INOX
Peso netto <i>Net weight (kg)</i>	6,0
Peso lordo <i>Gross weight (kg)</i>	8,0
Dimensione imballo <i>Packing dimensions (mm)</i>	B. 420 D. 350 H. 200




DIMENSIONE
PRODOTTO

B. 390 mm
D. 300 mm
H. 180 mm



FSV 33 IS

Alimentazione <i>Power supply (Volt/Hz)</i>	230 / 50-60
Potenza <i>Motor power (Kwatt/Hp)</i>	0,38 (0,50)
Barra saldante <i>Sealing bar (mm)</i>	330
Pompa per vuoto <i>Vacuum pump (L/min)</i>	13
Struttura <i>Structured in</i>	INOX
Peso netto <i>Net weight (kg)</i>	5,7
Peso lordo <i>Gross weight (kg)</i>	7,0
Dimensione imballo <i>Packing dimensions (mm)</i>	B. 420 D. 350 H. 200




DIMENSIONE
PRODOTTO

B. 390 mm
D. 300 mm
H. 180 mm



FSV 32T

Alimentazione <i>Power supply (Volt/Hz)</i>	230/50
Potenza <i>Motor power (Kwatt/Hp)</i>	0,4 (0,55)
Barra saldante <i>Sealing bar (mm)</i>	330
Pompa per vuoto <i>Vacuum pump (L/min)</i>	15 - autolubrificata
Struttura <i>Structured in</i>	ABS
Peso netto <i>Net weight (kg)</i>	5,0
Peso lordo <i>Gross weight (kg)</i>	5,5
Dimensione imballo <i>Packing dimensions (mm)</i>	B. 390 D. 330 H. 190




DIMENSIONE
PRODOTTO

B. 370 mm
D. 300 mm
H. 160 mm



FSV 32IT

Alimentazione <i>Power supply (Volt/Hz)</i>	230 / 50-60
Potenza <i>Motor power (Kwatt/Hp)</i>	0,4 (0,55)
Barra saldante <i>Sealing bar (mm)</i>	330
Pompa per vuoto <i>Vacuum pump (L/min)</i>	15 - autolubrificata
Struttura <i>Structured in</i>	INOX
Peso netto <i>Net weight (kg)</i>	7,0
Peso lordo <i>Gross weight (kg)</i>	7,5
Dimensione imballo <i>Packing dimensions (mm)</i>	B. 390 D. 330 H. 190




DIMENSIONE
PRODOTTO

B. 360 mm
D. 290 mm
H. 150 mm



FSV 35IT

Alimentazione <i>Power supply (Volt/Hz)</i>	230/50
Potenza <i>Motor power (Kwatt/Hp)</i>	0,4 (0,55)
Barra saldante <i>Sealing bar (mm)</i>	380
Pompa per vuoto <i>Vacuum pump (L/min)</i>	16
Struttura <i>Structured in</i>	INOX
Peso netto <i>Net weight (kg)</i>	8,0
Peso lordo <i>Gross weight (kg)</i>	9,0
Dimensione imballo <i>Packing dimensions (mm)</i>	B. 510 D. 320 H. 210



DIMENSIONE
PRODOTTO

B. 425 mm
D. 260 mm
H. 150 mm

FSV 45IT

Alimentazione <i>Power supply (Volt/Hz)</i>	230/50
Potenza <i>Motor power (Kwatt/Hp)</i>	0,5 (0,70)
Barra saldante <i>Sealing bar (mm)</i>	430
Pompa per vuoto <i>Vacuum pump (L/min)</i>	25 - autolubrificata
Struttura <i>Structured in</i>	INOX
Peso netto <i>Net weight (kg)</i>	10,0
Peso lordo <i>Gross weight (kg)</i>	11,0
Dimensione imballo <i>Packing dimensions (mm)</i>	B. 610 D. 330 H. 210




DIMENSIONE
PRODOTTO

B. 480 mm
D. 240 mm
H. 140 mm

FSV 521T

Alimentazione <i>Power supply (Volt/Hz)</i>	230 / 50-60
Potenza <i>Motor power (Kwatt/Hp)</i>	0,55 (0,75)
Barra saldante <i>Sealing bar (mm)</i>	550
Pompa per vuoto <i>Vacuum pump (L/min)</i>	30 - autolubrificata
Struttura <i>Structured in</i>	INOX
Peso netto <i>Net weight (kg)</i>	24,0
Peso lordo <i>Gross weight (kg)</i>	26,0
Dimensione imballo <i>Packing dimensions (mm)</i>	B. 770 D. 280 H. 290



DIMENSIONE
PRODOTTO

B. 600 mm
D. 310 mm
H. 160 mm

