



## VETRINETTE REFRIGERATE PER PIZZERIA

REFRIGERATED DISPLAY CASE FOR PIZZERIA

- Struttura interna ed esterna realizzata interamente in acciaio inox AISI 304
  - Refrigerazione statica
  - Gruppo incorporato
  - Termostato digitale per il controllo della temperatura
  - Spessore isolamento 40mm
  - Vetri di protezione inclusi
  - Idonee a contenere bacinelle gastronorm inox o in policarbonato con profondità massima di 150mm (bacinelle e coperchi esclusi)  
FV12033 5 x GN1/4  
FV15033 7 x GN1/4  
FV18033 9 x GN1/4  
FV20033 10 X GN1/4
  - Norme CE
- *Internal and external structure entirely made of AISI 304 stainless steel*
  - *Static refrigeration*
  - *Built-in refrigeration unit*
  - *Digital temperature control thermostat*
  - *Insulation thickness 40mm*
  - *Protection glass included*
  - *Suited for Gastronorm stainless steel or polycarbonate pans with a max depth of 150mm (pans and covers not included)*  
FV12033 5 x GN1/4  
FV15033 7 x GN1/4  
FV18033 9 x GN1/4  
FV20033 10 X GN1/4
  - *CE approved*




Iceline



## FV12033

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230/50
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,10 (0,14)
<b>Temperatura</b> <i>Temperature (°C)</i>	+2 +8
<b>Tipo refrigerante</b> <i>Refrigerant</i>	R134a
<b>Temperatura/Umidità</b> <i>Temperature/Humidity (°C/HR)</i>	+33 / 60
<b>Peso netto monofase</b> <i>Net weight single phase (kg)</i>	50,0
<b>Peso lordo monofase</b> <i>Gross weight single phase (kg)</i>	55,0
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 1270 D. 380 H. 410




DIMENSIONE  
PRODOTTO

B. 1200 mm  
D. 335 mm  
H. 435 mm



## FV15033

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230/50
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,13 (0,17)
<b>Temperatura</b> <i>Temperature (°C)</i>	+2 +8
<b>Tipo refrigerante</b> <i>Refrigerant</i>	R134a
<b>Temperatura/Umidità</b> <i>Temperature/Humidity (°C/HR)</i>	+33 / 60
<b>Peso netto monofase</b> <i>Net weight single phase (kg)</i>	58,0
<b>Peso lordo monofase</b> <i>Gross weight single phase (kg)</i>	63,0
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 1570 D. 380 H. 410




DIMENSIONE  
PRODOTTO

B. 1500 mm  
D. 335 mm  
H. 435 mm



## FV18033

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230/50
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,15 (0,20)
<b>Temperatura</b> <i>Temperature (°C)</i>	+2 +8
<b>Tipo refrigerante</b> <i>Refrigerant</i>	R134a
<b>Temperatura/Umidità</b> <i>Temperature/Humidity (°C/HR)</i>	+33 / 60
<b>Peso netto monofase</b> <i>Net weight single phase (kg)</i>	65,0
<b>Peso lordo monofase</b> <i>Gross weight single phase (kg)</i>	70,0
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 1870 D. 380 H. 410




DIMENSIONE  
PRODOTTO

B. 1800 mm  
D. 335 mm  
H. 435 mm

## FV20033

<b>Alimentazione</b> <i>Power supply (Volt/Hz)</i>	230/50
<b>Potenza</b> <i>Motor power (Kwatt/Hp)</i>	0,15 (0,20)
<b>Temperatura</b> <i>Temperature (°C)</i>	+2 +8
<b>Tipo refrigerante</b> <i>Refrigerant</i>	R134a
<b>Temperatura/Umidità</b> <i>Temperature/Humidity (°C/HR)</i>	+33 / 60
<b>Peso netto monofase</b> <i>Net weight single phase (kg)</i>	70,0
<b>Peso lordo monofase</b> <i>Gross weight single phase (kg)</i>	75,0
<b>Dimensione imballo</b> <i>Packing dimensions (mm)</i>	B. 2070 D. 380 H. 410



DIMENSIONE  
PRODOTTO

B. 2000 mm  
D. 335 mm  
H. 435 mm