

# FABB5



- Professional equipment
- Inside and outside made of Stainless Steel, except for the external bottom made of Galvanized Steel
- Internal rounded corners
- Insulation in CFC free polyurethane high pressure injected
- Insulation thickness 60 mm
- Self-closing door with magnetic gaskets
- The core probe is included
- Electronic front control panel with room probe and temperature core probe (digital model)
- Capacitive touch digital control panel with digital display (positive blast chilling, negative shock freezing, blast chilling temperature, core probe temperature, blast chilling time, conservation) (digital touch model)
- Ventilated cooling with air shaker
- Tropicalized and easy extractable condensing unit (ambient temperature +43 °C and relative humidity of 65%)
- Time evaporator defrosting (made at the end of the cycle) and lower condense water tray
- Suitable for 5 trays GN 1/1 or 600x400 mm
- Trays not included
- CE approved
- Proudly Made in Italy

## TECHNICAL SHEET

<b>Power supply (Volt/Hz)</b>	230/50
<b>Temperatura (°C)</b>	+3 / -40
<b>Tipo refrigerante</b>	R452a / R507a
<b>Dimensioni interne (mm)</b>	610x410x410
<b>Capacità (lt)</b>	5 - GN 1/1 - 5 - 600x400
<b>Net weight single phase (kg)</b>	92,0
<b>Gross weight single phase (Kg)</b>	98,0
<b>Dimensions (mm)</b>	B. 750 D. 740 H. 870
<b>Packaging dimensions (mm)</b>	B. 800 D. 800 H. 900