

# FBR2100TN



- Professional equipment
- Internal and external structure entirely made of stainless steel
- Back panel in stainless steel
- Ventilated refrigeration with anticorrosion treated evaporator
- Digital thermostat for temperature control and defrosting
- Cold air recirculation
- Incorporated refrigeration unit
- Electrical heating element around door frame to eliminate condensation
- Automatic condensation evaporation
- 60mm insulation thickness
- Easily removable magnetic gasket
- Internal rounded edges for easy cleaning
- Front panel with keylock
- Adjustable stainless steel feet
- Inclusive of 1 pcs GN 1/1 shelf and guide (for door)
- CE approved

## TECHNICAL SHEET

<b>Power supply (Volt/Hz)</b>	230/50
<b>Power (Kwatt/Hp)</b>	0,3 (0,4)
<b>Temperatura (°C)</b>	-2 +8
<b>Tipo refrigerante</b>	R134a
<b>Temperatura/Umidità (°C/HR)</b>	+43 / 60
<b>Dimensioni interne (mm)</b>	902x530 h.589
<b>Capacità (lt)</b>	282
<b>Net weight single phase (kg)</b>	98,0
<b>Gross weight single phase (Kg)</b>	113,0
<b>Dimensions (mm)</b>	B. 1360 D. 700 H. 860
<b>Packaging dimensions (mm)</b>	B. 1390 D. 730 H. 910