

FFR1400TN



- Professional equipment
- TN normal temperature (0° +10°)
- Inside and outside made of stainless steel, except for external bottom, external ceiling and back made of galvanized steel
- Insulation in CFC free polyurethane high pressure injected
- Insulation thickness: 60 mm
- Ventilated cooling
- Tropicalized and extractable "monoblock type" condensing unit (ambient temperature +40°C and relative humidity of 60%)
- Complete automatic defrosting and condensing water evaporation
- Automatic closing doors with magnetic seal, and ergonomic handle, easy to open
- Electronic front control panel with NTC probe
- Internal rounded corners
- Adjustable Stainless Steel feet (110/190 H mm)
- Standard fan brake
- Luxury model (automatic defrosting resistance as standard, internal lighting standard – low consumption led lighting, lock standard)
- Inclusive of GN 2/1 and hook kit (6 pcs.)
- CE approved
- Proudly Made in Italy

TECHNICAL SHEET

| | |
|---------------------------------------|------------------------|
| Power supply (Volt/Hz) | 230/50 |
| Power (Kwatt/Hp) | 0,57 (0,75) |
| Temperatura (°C) | 0 / +10 |
| Tipo refrigerante | R404a / R507a |
| Temperatura/Umidità (°C/HR) | +40 / 60% |
| Capacità (lt) | 1400 |
| Net weight single phase (kg) | 150,0 |
| Gross weight single phase (Kg) | 160,0 |
| Dimensions (mm) | B. 1420 D. 800 H. 2100 |
| Packaging dimensions (mm) | B. 1460 D. 840 H. 2200 |