

FTR3TN



- Professional equipment
- Refrigerated Pizza Counter 700 mm depth, for plasticized shelves and containers GN 1/1
- 1 tray and 1 pair of guides included
- TN normal temperature (-2° +8°)
- Inside and outside made of Stainless Steel, except for the external bottom made of Galvanized Steel
- Internal rounded corners
- Insulation in CFC free polyurethane high pressure injected
- Insulation thickness NT counters: 40 mm
- Self-closing doors with magnetic gaskets
- Electronic front control panel with NTC probe
- Ventilated cooling
- Tropicalized and extractable "monoblock type" condensing unit (ambient temperature +40°C and relative humidity of 60%)
- Complete automatic defrosting and condensing water evaporation
- Adjustable Stainless Steel feet (110/190 H mm)
- Backsplash on request
- CE approved
- Proudly Made in Italy

TECHNICAL SHEET

Power supply (Volt/Hz)	230/50
Power (Kwatt/Hp)	0,495
Temperatura (°C)	0 / +10
Tipo refrigerante	R452a / R507
Temperatura/Umidità (°C/HR)	+40 / 60%
Capacità (lt)	460
Net weight single phase (kg)	102,0
Gross weight single phase (Kg)	112,0
Dimensions (mm)	B. 1870 D. 700 H. 850/920
Packaging dimensions (mm)	B. 1920 D. 740 H. 1000